

TRI- MIX PC 500

High Range Water-Reducing, polycarboxylate ether Admixture for Concrete.

Description

TRI-MIX PC 500 is a high range water reducing new generation super plasticizer that greatly decreases water / cement ratio to increase workability and mechanical properties of concrete.,

TRI-MIX PC 500 is a ready to use transparent liquid concrete admixture based on selected and highly purified special synthetic chemicals and instantly dispersible in water, which allow mixing water to be reduced considerably and concrete strength to be enhanced significantly particularly at early ages.



Standard compliance

- BS –EN934 -2
- ASTM C494 (Type A, F)

Typical uses

Tri- Mix PC 500 can be used with all types of cement to achieve the required properties in the following items:

- Pre- cast concrete.
- Ready-mixed concrete.
- Pumped concrete.
- Reinforcement, Slabs and foundations, Bridge, Beams and ceilings.
- To producing high quality interlock.

Advantages

- Improve workability, with easier and quicker placing and compaction.
- Normal set without retardation.
- Improves the quality, density, compressive strength and surface finish of concrete.
- Reduce shrinkage and creep.

Technical Data @°25c

Appearance @ 25° C	transparent liquid
Solid Content	50 ±1
Specific Gravity @ 20° C	1.09 - 1.11
Chloride content	< 0.1
Alkali Content	< 1

Directions for use

Tri- Mix PC 500 should be added to the mix with the gauging water (after adding 50-70% of water), also it can also be added to the water prior to mixing, and also it can be used as post addition on the site.

Rate of use

Tri- Mix PC 500 can be used at the dose rate (0.3 - 1.5 %) of total binder, depending on requirements concerning workability and strength. It is recommended that trial mixes be conducted to determine the exact dosage rate required where the dose depend on the require application and W/C ratio, type of cement, aggregates and on temperature.

Package

- **Tri- Mix PC 500** : Drum 200 liter and 1000 liter / or as customer requirements.

Storage conditions

- Store the material in a cool, dry and covered place.
- Temperature should not exceed 35 °C.
- Do not expose the pails to direct sunlight and keep away from all sources of heat.
- 12 months in dry conditions at temperatures between +5 °C and +45

Shelf life

- **Tri- Mix PC 500** a shelf life of 12 month stored in dry and cool place

Cleaning

Tools should be cleaned immediately with water after use.

Hardened material can only be removed mechanically.

Sustainability and environmental accountability

- TRI-CHEM's Environmental sustainability is the accountability to conserve natural resources and protect global ecosystems to support health and well-being for this a more positive approach is that accountability guides the actions of power-holders towards more socially and environmentally sustainable results.

Technical support

- For any technical support, please contact TRI-CHEM technical office or representatives.

Health and safety responsibility

- Workplace health and safety is all about sensibly managing risks to protect TRI-CHEM's workers and business.
- ISO 45001 is a systematic health and safety management is characterized by strong leadership involving managers, workers, suppliers, contractors and customers and also health and safety management is an essential part of the movement towards sustainable development.
- Spillages should be washed down immediately.
- PPE in accordance with the health and safety rules should be used during the materials application.
- For irritant effects of the non-cured material, avoid contact with skin and eyes during storage and application.

Institutional Excellence and quality performance

- Institutional excellence in TRI-CHEM refers to achieving high levels of performance, quality and effectiveness in all aspects of TRI-CHEM company's work, it involves a systematic and continuous effort to improve an organization's performance by applying best practices, innovative approaches and evidence-based strategies, institutional excellence spans various areas, such as training , research, innovation, community engagement, governance, management and sustainability, and involves setting high standards, measuring performance against these standards and continuously improving performance to meet or exceed these standards, excellence in TRI-CHEM also includes a culture of continuous improvement and learning, where everyone in the organization is committed to achieving the organization's goals, working together to find solutions to challenges and opportunities, and requires a collaborative approach that includes all stakeholders.
- All products originating from TRI-CHEM facility are manufactured under a quality management system independently certified to conform the requirements of the quality standards (ISO 9001:2015).

Disclaimer

- While TRI-CHEM guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control.
- TRI-CHEM is recommended to verify with TRI-CHEM that the product is suitable for the intended use, and that this data sheet version is the latest one.
- TRI-CHEM may modify it without prior notice and technical characteristics are listed for guidance only.
- Any specification, recommendation or information mentioned in this product data sheet is (to TRI-CHEM's best knowledge) true and reliable.
- However, because TRI-CHEM has no influence on the application method of these products and the care taken, the company cannot accept any liability arising from the use of its products.

TRI-CHEM's warranty is therefore limited to the quality of the materials supplied which are guaranteed against defective materials.

**Factory & Head Office:**

6 October City - 4th Industrial Zone - Al Oula Industrial Zone Plot No.: 14
Tel.: (002) 011 195 48267 - Sales: (002) 010 007 88817 - (002) 011 184 87597
Technical Support Call : (002) 011 184 87880 - Email: sales@tichem-eg.com

www.trichem-eg.com

