

TRI-CURE WB

Water based concrete curing compound.

Description

TRI-CURE WB is a water based curing compound used for spraying into the Surface of concrete To provide an effective and economical method of curing and prevention of Premature water loss in concrete.



Standards complianc

Product certified by (National Research Centre)

ASTM C 309

(type 1 - class A)

Mode of Action

TRI-CURE WB forms a film retains sufficient moisture in the concrete to ensure full hydration of the cement essential for optimum strength development. Membrane-cured concrete is typically harder and exhibits a dust-free surface with a reduced incidence of drying shrinkage cracks.

TRI-CURE WB life cycle,s of the formed film is depended on many variables which included the application of film formation, thickness, UV, concrete porosity and the degree of exposure to weathering.

NOTE

In some application or if needed **Tri-Cure** should be removed by sand blasting or by the mechanical facilities before applying any coating or renders.

Typical uses

TRI-CURE WB is used for :-

Provide a resin membrane on the surface on newly placed concrete to retain moisture for effective curing to take place so it is suitable for all general concreting applications.

Advantages

- Easy of application.
- Reduces labor costs.
- Enables concrete to hydrate effectively.
- Reduces surface shrinkage and cracking.
- No waiting – apply as soon as possible after placing concrete.

Technical Data @°25c

Appearance	Milky color
Density	1.0 ± 0.01 kg/L
Rate of use	6 -8 m2 / L (depend on surface conditions)
Water retention after 72 hrs	0.55 kg / m2
Drying time @ 23 °C	1-1.30 HRS

Directions for use

TRI-CURE WB can be applied by spraying machine or a roller to the surface of the newly placed concrete , care Should be taken to ensure a complete covering .

TRI-CURE WB should be applied as soon as possible after the concrete has been surface finished , but generally within 30 - 60 minutes depending on weather condition.

Package

- **TRI-CURE WB** is available in 5- 20 liter and 200 LIT.

Cleaning

- **TRI-CURE WB** immediately after use the spraying equipment should be cleaned out with Thinner .

Shelf life

- 12 month stored in dry and cool place.

Storage conditions

- Store the material in a cool, covered dry place.
- Temperature should not exceed 35 °C.
- Do not expose the pails to direct sunlight and keep away from all sources of heat.

Sustainability and environmental accountability

- TRI-CHEM's Environmental sustainability is the accountability to conserve natural resources and protect global ecosystems to support health and well-being for this a more positive approach is that accountability guides the actions of power-holders towards more socially and environmentally sustainable results.

Technical support

- For any technical support, please contact TRI-CHEM technical office or representatives.

Health and safety responsibility

- Workplace health and safety is all about sensibly managing risks to protect TRI-CHEM's workers and business.
- ISO 45001 is a systematic health and safety management is characterized by strong leadership involving managers, workers, suppliers, contractors and customers and also health and safety management is an essential part of the movement towards sustainable development.
- Spillages should be washed down immediately.
- PPE in accordance with the health and safety rules should be used during the materials application.
- For irritant effects of the non-cured material, avoid contact with skin and eyes during storage and application.

Institutional Excellence and quality performance

- Institutional excellence in TRI-CHEM refers to achieving high levels of performance, quality and effectiveness in all aspects of TRI-CHEM company's work, it involves a systematic and continuous effort to improve an organization's performance by applying best practices, innovative approaches and evidence-based strategies, institutional excellence spans various areas, such as training , research, innovation, community engagement, governance, management and sustainability, and involves setting high standards, measuring performance against these standards and continuously improving performance to meet or exceed these standards, excellence in TRI-CHEM also includes a culture of continuous improvement and learning, where everyone in the organization is committed to achieving the organization's goals, working together to find solutions to challenges and opportunities, and requires a collaborative approach that includes all stakeholders.
- All products originating from TRI-CHEM facility are manufactured under a quality management system independently certified to conform the requirements of the quality standards (ISO 9001:2015).

Disclaimer

- While TRI-CHEM guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control.
- TRI-CHEM is recommended to verify with TRI-CHEM that the product is suitable for the intended use, and that this data sheet version is the latest one.
- TRI-CHEM may modify it without prior notice and technical characteristics are listed for guidance only.
- Any specification, recommendation or information mentioned in this product data sheet is (to TRI-CHEM's best knowledge) true and reliable.
- However, because TRI-CHEM has no influence on the application method of these products and the care taken, the company cannot accept any liability arising from the use of its products. TRI-CHEM's warranty is therefore limited to the quality of the materials supplied which are guaranteed against defective materials.

Factory & Head Office:

6 October City - 4th Industrial Zone - Al Oula Industrial Zone Plot No.: 14
Tel.: (002) 011 195 48267 - Sales: (002) 010 007 88817 - (002) 011 184 87597
Technical Support Call : (002) 011 184 87880 - Email: sales@trichem-eg.com
www.trichem-eg.com